



The foundation of Blue Coat's application delivery infrastructure, Blue Coat ProxySG® appliances establish points of control that accelerate and secure business applications for users across the distributed organization. As the world's leading proxy appliance, the Blue Coat ProxySG is a powerful yet flexible tool for improving both application performance and security, removing the need for compromise.

## FEATURES

### Acceleration — MACH5

#### Bandwidth Management

- > Assign priority and network resources based on port, device, applications or content to reflect corporate policies

#### Protocol Optimization

- > Improve inefficient protocols by making them more tolerant to higher latencies

#### Byte Caching

- > Cache repetitive traffic found in the byte stream and serve it locally to reduce WAN traffic

#### Object Caching

- > Store files, videos and Web content locally, providing LAN-like performance over WAN

#### Compression

- > Inline compression can reduce predictable patterns even on the first pass

#### MACH5 Acceleration Client

- > SG Client software extends MACH5 acceleration capabilities to remote users connecting over VPNs or the WAN

### Control — Proxy Services

#### Proxy support for multiple protocols

- > HTTP, CIFS, SSL, FTP, MAPI, P2P, MMS, RTSP, QuickTime, TCP-Tunnel, DNS
- > Bandwidth management on all proxy services
- > SSL Termination & Proxy (forward and reverse)
- > Control encrypted traffic for all users and applications inside & outside the enterprise

#### Content Filtering and Security

- > On-proxy support of leading URL lists, popular regional lists, custom lists, or custom categories
- > Strip and replace Web content P2P file sharing controls
- > Log and block P2P traffic
- > Control BitTorrent, eDonkey, Gnutella, and FastTrack

#### Web virus scanning

- > ProxyAV integration with ProxySG
- > Choice of anti-virus engines

#### IM Logging and Controls

- > MSN, Yahoo!, AOL Messengers
- > Method level control settings

### Spyware Prevention and Control

- > Block spyware and malware
- > Control pop-ups and phishing scams

#### Streaming controls

- > MS, Real, QuickTime
- > Stream splitting & caching

### Performance & Reliability — SGOS

#### Platform highlights:

- > Secure object-based operating system with small footprint
- > High-speed caching with advanced object pipelining and adaptive refresh
- > Built-in pass-through network card, compression services, bandwidth management, and SSL off loading

#### Network functionality including:

- > Active/Active bridging support using virtual IP addressing for failover and remote installations
- > Routing configurations for gateway, route tables, RIP, DNS, and WCCP
- > Health checks performed on a forwarding host or external servers to verify status and availability of device
- > 19" Rack mountable (with kit) or portable use Integrated support services
- > View & submit service requests via the Blue Coat management interface
- > Send snapshots (trace files) to Blue Coat Support Services for faster resolution

### Manageability — Policy Processing Engine

#### Authentication

- > Utilize a company's existing authentication source for integrated SSO, including local password files, NTLM, LDAP (Active Directory, eDirectory, SunOne), CA eTrust SiteMinder, Microsoft Kerberos, Oracle Access Manager, RADIUS and certificates
- > Multi-realm authentication sequencing
- > Forms-based authentication support

#### Powerful management interface

- > Web-based management interface
- > Optional command line interface

- > Alerting via SNMP, SMTP and logging administrative events

### Comprehensive policy definitions

- > Graphical Visual Policy Manager with layered policy definitions
- > Definable triggers and actions for policy definition

### Content Policy Language (CPL)

- > Create custom text-based policies to address unique policy requirements
- > Built-in text editor for CPL allows sample code to be copied and pasted from Blue Coat TechBriefs or Support Services advisories

### Extended Management with Director

- > Distribute, backup, restore policy files for multiple Blue Coat ProxySG appliances
- > Manage policy by device, group, or region
- > Job scheduling/job status reporting

### Management & Control of SG Clients

- > Configure, provision and maintain global deployment of SG Clients
- > Accelerate applications by user
- > Upgrade client versions seamlessly with auto version detection and update

### Visibility — Management Reporting

#### Default logging

- > HTTP, HTTPS, CIFS, MAPI, FTP, TCP-Tunnel, P2P, ICP, Windows Media, Real Media, QuickTime, DNS
- > Global log file limits and upload sizing
- > Client upload settings and scheduling

#### Custom logging and trace files

- > Selectable fields/text/log formats

#### Statistics

- > Bandwidth Gain
- > HTTP/HTTPS/FTP history
- > Streaming history
- > Resources

#### SNMP Support

- > Trap settings, community strings

### Aggregate Blue Coat ProxySG Logs with Reporter

- > Reporter Dashboard™ provides a "drill-able" overview of Web activity
- > 150+ pre-defined reports track user activity, security risks, and Web traffic performance
- > Secure browser access/role-based viewing
- > Provides real-time reporting with continuous log uploads



SG210 SERIES	SG210-5	SG210-10	210-25	Physical Properties
<b>License Capacity - Concurrent Users</b>				<b>Dimensions and Weight</b>
With ADN Enabled	10	50	Unlimited	
Without ADN Enabled	30	150	Unlimited	Desk/wall mount, rack mountable* [*specific rack mount kit required].
<b>System</b>				Dimensions (L x W x H)
Disk drives	1x80GB IDE	1x250GB IDE	1x250GB IDE	35.6cm x 19.1cm x 4.4cm (14in x 7.5in x 1.72in)
RAM	512MB	1GB	1GB	Weight (maximum)
Network Interfaces	(2) integrated (on board) 10/100Base-T NICs with passthrough	(2) integrated (on board) 10/100Base-T NICs with passthrough	10/100Base-T NICs with passthrough	2.6kg(5.8lb)
Optional NICs/Cards	SSL Offload Card	None	None	<b>Operating Environment</b>
				Power
				AC power 100-240V, 50-60Hz, 6.3-3.0A
				Maximum Power
				45 Watts
				Thermal Rating
				153.63 BTU/Hr
				Temperature
				5°C to 35°C (41°F to 95°F)
				Humidity
				Less than 90% relative humidity, non-condensing
				Altitude
				Up to 3048 M (10,000 ft)

SG510 SERIES	SG510-5	SG510-10	SG510-20	SG510-25	Physical Properties
<b>License Capacity - Concurrent Users</b>					<b>Dimensions and Weight</b>
With ADN Enabled	50	125	300	Unlimited	
Without ADN Enabled	200	500	1200	Unlimited	19" Rack-mountable
<b>System</b>					Dimensions (L x W x H)
Disk drives	2x80GB SATA	2x320GB SATA	2x320GB SATA	2x320GB SATA	58cm x 44cm x 4.4cm (22.8in x 17.4in x 1.7in)
RAM	2GB RAM	2GB RAM	2GB RAM	2GB RAM	Weight (maximum)
Network Interfaces	(2) integrated (on board) 10/100/1000 Base-T NICs	(2) integrated (on board) 10/100/1000 Base-T NICs	10/100/1000 Base-T NICs	2x10/100/1000 Base-T card (dual GigE with passthru)	12.3kg(27lb) 12.7kg(28lb) 12.7kg(28lb) 12.7kg(28lb)
Optional Cards	SSL Offload card	None			<b>Operating Environment</b>
Optional NICs	2x10/100/1000Base-T card (dual GigE)				Power
	2x10/100/1000Base-SX card (dual GigE Fibre)				AC power 100-240V, 50-60Hz, 6.3-3.0A
	4x10/100/1000Base-T card (quad GigE with passthru)				Maximum Power
					150 Watts
					Thermal Rating
					512 BTU/Hr
					Temperature
					5°C to 35°C (41°F to 95°F)
					Humidity
					Less than 90% relative humidity, non-condensing
					Altitude
					Up to 3048m (10,000ft)

SG810 SERIES	SG810-5	SG810-10	SG810-20	SG810-25	Physical Properties
<b>License Capacity - Concurrent Users</b>					<b>Dimensions and Weight</b>
With ADN Enabled	500	700	1000	Unlimited	
Without ADN Enabled	2500	3500	5000	Unlimited	19" Rack-mountable
<b>System</b>					Dimensions (L x W x H)
Disk drives	2x73GB SCSI Ultra 320	2x300GB SCSI Ultra 320	4x300GB SCSI Ultra 320	4x300GB SCSI Ultra 320	58cm x 44cm x 4.4cm (22.8in x 17.4in x 1.7in)
RAM	2GB RAM	4GB RAM	6GB RAM	6GB RAM	Weight (maximum)
Network Interfaces	(2) integrated (on board) 10/100/1000 Base-T NICs	(2) integrated (on board) 10/100/1000 Base-T NICs	10/100/1000 Base-T NICs	2x10/100/1000 Base-T card (dual GigE with passthru)	14.1kg(31lb) 14.5kg(32lb) 15.4kg(34lb) 15.4kg(34lb)
Optional Cards	SSL Offload card	None			<b>Operating Environment</b>
Optional NICs	2x10/100/1000Base-T card (dual GigE)				Power
	2x10/100/1000Base-SX card (dual GigE Fibre)				AC power 100-240V, 50-60Hz, 6.3-3.0A
	4x10/100/1000Base-T card (quad GigE with passthru)				Maximum Power
					375 Watts
					Thermal Rating
					1280.25 BTU/Hr
					Temperature
					5°C to 35°C (41°F to 95°F)
					Humidity
					Less than 90% relative humidity, non-condensing
					Altitude
					Up to 3048m (10,000ft)

SG8100 SERIES	SG8100-5	SG8100-10	SG8100-20	Physical Properties
<b>License Capacity - Concurrent Users</b>				<b>Dimensions and Weight</b>
With/Without ADN Enabled	Unlimited	Unlimited	Unlimited	
<b>System</b>				19" Rack-mountable
Disk drives	2x300GB SCSI Ultra 320	4x300GB SCSI Ultra 320	8x300GB SCSI Ultra 320	Dimensions (L x W x H)
RAM	4GB RAM	6GB RAM	8GB RAM	59.2cm X 44.2cm X 17.652cm (23.3in X 17.4in X 6.95in)
Network Interfaces	(2) integrated (on board) 10/100/1000 Base-T NICs	(2) integrated (on board) 4x10/100/1000Base-T NICs	10/100/1000 Base-T NICs	Weight (maximum)
Optional Cards	SSL Offload card - only available for 8100-5	Dual GigE NIC card	SSL card	25.4kg(56lb) 27.2kg(60lb) 2308kg(68lb)
Optional NICs	2x10/100/1000Base-T card (dual GigE)			<b>Operating Environment</b>
	4x10/100/1000Base-T card (quad GigE)			Power
	4x10/100/1000Base-SX card (quad GigE Fibre)			AC power 100-240V, 50-60Hz, 6.3-3.0A
				Maximum Power
				525 Watts
				Thermal Rating
				1792 BTU/Hr
				Temperature
				5°C to +40°C (41°F to 104°F)
				Humidity
				Less than 90% relative humidity, non-condensing
				Altitude
				Up to 3000 M (9,483 ft)

FOR ALL SG SERIES	
<b>Regulations</b>	
Emissions	FCC Class A, EN55022 Class A, VCCI Class A No.1706609, BSMI, CCC, C-tick
Safety	CSA C22.2 No. 950 M95, UL 60950 3rd Edition, EN60950, TUV-GS, TUV-S, CCC, BSMI
Standards	UL/CSA, TUV-S, BSMI, C-tick, CCC, CE
<b>Support Standard Warranty</b>	90-day software & phone support with 1-year hardware support; extended and upgraded support plans available

Blue Coat Systems, Inc. 1.866.30.BCOAT // 408.220.2200 Direct • 408.220.2250 Fax • [www.bluecoat.com](http://www.bluecoat.com)

Copyright © 2007 Blue Coat Systems, Inc. All rights reserved worldwide. No part of this document may be reproduced by any means nor translated to any electronic medium without the written consent of Blue Coat Systems, Inc. Specifications are subject to change without notice. Information contained in this document is

believed to be accurate and reliable, however, Blue Coat Systems, Inc. assumes no responsibility for its use. Blue Coat is a registered trademark of Blue Coat Systems, Inc. in the U.S. and worldwide. All other trademarks mentioned in this document are the property of their respective owners. v.DS-SGOS-v1.2 - 0108